



C	芯片型号 Sensor Type	2/3"	MAX Image Circle (2y=11.2)
C	分辨率 Resolution Ratio	5um	Image Space
C	机械后焦 Flange Distance	17.526mm ± 0.05mm	In Air
C	接口 Mount	C	-
C	焦距 EFL	12.2mm ± 5%	-
C	倍率 Magnification	4.0X ± 5%	-
D	工作距离 Work Distance	110mm ± 3mm	-
D	共轭距离 Conjugate Distance	262.0mm ± 5mm	-
D	工作光圈 WFNO	22.0 ± 5%	At Work Distance
D	远心度 Telecentricity	0.1° ± 5%	Object Space
D	景深 DOF	0.06mm ± 5%	At F22.0
E	光学畸变 Optical Distortion	0.02% ± 5%	At 2y=11.2
E	相对照度 Relative Illumination	99.8% ± 5%	At 2y=11.2

公差 线性尺寸 公差	>0.5-6	±0.05	公差 角度尺寸 公差	>0-10	±1°	材料			
	>6-30	±0.1		>10-50	±30'				
	>30-120	±0.15		>50-120	±20'				
	>120-400	±0.2		>120-400	±10'				
设计						审核	批准		
Y J									
'21.01.05									
图样标记						单位	比例	数量	页码
标记 处数 位置分区 变更号 签字 日期						mm	1:1	1	1/1

DZO 东正光学
DongZheng Optics

名称
TC400110A_外形规格图

图号



描图
旧底图登记号
底图登记号