



芯片型号Sensor Type	2/3"	MAX Image Circle (2y=11.2)
分辨率Resolution Ratio	5um	Image Space
机械后焦Flange Distance	17.526mm ± 0.05mm	In Air
接口Mount	C	-
焦距EFL	82.8mm ± 5%	-
倍率Magnification	1.5X ± 5%	-
工作距离Work Distance	110mm ± 3mm	-
共轭距离Conjugate Distance	256.4mm ± 5mm	-
工作光圈WFNO	10.0 ± 5%	At Work Distance
远心度Telecentricity	0.1° ± 5%	Object Space
景深DOF	0.18mm ± 5%	At F10.0
光学畸变Optical Distortion	0.04% ± 5%	At 2y=11.2
相对照度Relative Illumination	99.3% ± 5%	At 2y=11.2

线性尺寸公差	>0.5-6	±0.05	角度尺寸未注公差	>0-10	±1°	材料	名称 TL150110A_外形规格图		
	>6-30	±0.1		>10-50	±30'				
	>30-120	±0.15		>50-120	±20'				
	>120-400	±0.2		>120-400	±10'				
设计						审核	批准		
Y J							图号		
'21.01.04									
图样标记						单位	比例	数量	页码
mm						1:1	1	1/1	
标记	处数	位置分区	变更号	签字	日期				



描图
旧底图登记号
底图登记号