


C	芯片型号 Sensor Type	2/3"	MAX Image Circle (2y=11.2)
C	分辨率 Resolution Ratio	5um	Image Space
C	机械后焦 Flange Distance	17.526mm ± 0.05mm	In Air
C	接口 Mount	C	-
D	焦距 EFL	43.4mm ± 5%	-
D	倍率 Magnification	2.0X ± 5%	-
D	工作距离 Work Distance	65mm ± 3mm	-
D	共轭距离 Conjugate Distance	162.5mm ± 5mm	-
D	工作光圈 WFNO	13.2 ± 5%	At Work Distance
E	远心度 Telecentricity	0.15° ± 5%	Object Space
E	景深 DOF	0.13mm ± 5%	At F13.0
E	光学畸变 Optical Distortion	0.045% ± 5%	At 2y=11.2
E	相对照度 Relative Illumination	98.8% ± 5%	At 2y=11.2

公差 线性尺寸 公差	>0.5-6	±0.05	公差 角度尺寸 公差	>0-10	±1°	材料			
	>6-30	±0.1		>10-50	±30'				
	>30-120	±0.15		>50-120	±20'				
	>120-400	±0.2		>120-400	±10'				
描图						设计	审核	批准	
旧底图登记号						Y J			
底图登记号						'21.01.04			
标记	处数	位置分区	变更号	签字	日期	图样标记			
						单位	比例	数量	页码
						mm	1:1	1	1/1



名称
TL200065A_外形规格图

图号



描图

旧底图登记号

底图登记号

标记